



BioGuard™ SHOCK is a fast-acting, non-oxidizing membrane-safe biocide for industrial applications. Effective against a broad spectrum of bacteria, BioGuard™ SHOCK can also be applied to control fungi and algae. This fast-acting biocide breaks down quickly, and as such does not present the same long term environmental impact as other biocides.

Features / Benefits

- Contains 20% active 2, 2-dibromo-3nitrilopropionamide (DBNPA)
- Provides broad-spectrum control of bacteria
- Fast-acting membrane compatible microbiocide
- Breaks down at neutral to high pH
- Neutralizes by sodium bisulfite

Uses

- Used online or as intermittent Clean In Place
- Control of bacterial, algae and fungi in membrane systems

Specifications

Appearance	Yellow to amber liquid
pH	1.8 - 2.0
Density (kg/liter)	1.2 - 1.3

Packaging

Pail: 5 gallon/18.9 liter

Tote: 275 gallon/1,040 liter

Drum: 55 gallon/208 liter

Bulk: available upon request

For special packaging options, please contact PWT or your local distributor.

BioGuard™ SHOCK
LIQUID BIOCIDES

BioGuard™ SHOCK

LIQUID BIOCIDE

General Mixing & Application Instructions for BioGuard™ SHOCK

1. Feed product neat from shipping container
2. Typical dose rates are 100 ppm as Clean In Place, circulate for 30 minutes
3. Can be fed as online shock treatment at 20 ppm for 1-2 hours for non potable systems
4. Call Professional Water Technologies or your local distributor for custom chemical dosing recommendation.

ProDose XPRT™ – Scaling Prediction Software

ProDose XPRT™ uses the most accurate scaling prediction calculations available to accurately determine effective antiscalant dosage, and cleaning chemical usage. The user can enter multiple cases to study various operating conditions, directly enter concentrate analysis, and select the best PWT product and dosage for the application.

ProDose XPRT™ is available upon request only. Please contact your PWT representative for more information.

The screenshot displays the PWT ProDose software interface. At the top, there is a navigation bar with various parameters: UNITS (US), TEMPERATURE (Fahrenheit), PERMEATE FLOW (81.00), RECOVERY (75.0%), ANTISCALANT (SpectraGuard Liquid), DOSAGE (2.95 PPM), SOURCE (Well Water), PROJECT NAME (Project 1), and CASE (1). Below this, a sidebar on the left contains menu items: PROJECT INFORMATION, WATER QUALITY, SYSTEM INFORMATION, CHEMICAL SELECTION, CALCULATIONS, and REPORT. The main content area is divided into several sections: OVERVIEW (with fields for CLIENT NAME, PROJECT NAME, LOCATION, PREPARED BY, DATE, and WATER TYPE), MEASUREMENTS (with dropdowns for PRESET UNITS, TEMPERATURE, FLOW RATES, and MASS UNITS), COMMENTS (OPTIONAL) (a text area), and TOTAL CASES (1 AVAILABLE) (a table with columns for Cases and Modified Date). The table shows one case with ID 1 and a modified date of 5/27/2016. Below the table is a field for Selected Case Description.



PWT Headquarters & Manufacturing
1048 La Mirada Court, Vista, California 92081

Toll-Free: 800.914.9072 | Direct: 760.639.4400 | Fax: 760.639.4439
Email: sales@pwtchemicals.com | www.pwtchemicals.com